



MileGuard™ Full Synthetic SAE 5W-30 Dexos1 GenII Motor Oil

MileGuard Full Synthetic SAE 5W-30 Dexos1® GenII Motor Oil is a top tier, high detergent automotive engine oil specially formulated to meet the stringent lubrication requirements of today and tomorrow's engines. It meets API SN+ which is required for 2012 and later engines. Synthetic base oils combine with carefully selected additive packages to provide maximum protection against wear, rust, corrosion, oxidative thickening, acid formation, sludge and varnish.

MileGuard Full Synthetic SAE 5W-30 Dexos1® GenII Motor Oil is specifically formulated to deliver increased fuel economy, and protection from frequent re-starts that occur in some hybrid vehicles. The science of using synthetic base stocks in SAE 5W-30 viscosity grade translates into outstanding engine protection when operating in both high and low temperature environments

MileGuard Full Synthetic SAE 5W-30 Dexos1® GenII Motor Oil is a licensed GM is a licensed GM dexos1 GenII product (GM License #D10840IF198). Meets or exceeds API Service Category SN+, SM, SL, SJ, and ILSAC GF-5 requirements. Exceeds the performance requirements of Toyota and Honda.

Benefits

- Formulated to reduce friction and provide increased fuel economy
- Protects engine in all temperatures and conditions
- Keep precision parts running clean
- ILSAC GF-5 resource conserving

Meets or Exceeds

- GM Dexos1 Gen II (License #D10840IF198)
- ILSAC GF-5
- API Service Category SN+, SM, SL, SJ

Part Numbers

- Bulk - 27712B
- 55 Gallon Drum – 27712
- 6x1 Quart Case - 401424



Tilley Company Inc.

1211 Belmar Drive Belcamp, MD 21017

410-574-4500

www.tilleylubricants.com



Typical Characteristics

SAE Grade	5W-30
API Gravity @ 60°F	33.7
Sp. Gr. @ 60°F	0.8490
Flash, COC, °F	405
Pour Pt., °F	-40
Viscosity,	
cSt @ 40°C	56.7
cSt @ 100°C	9.9
Viscosity Index	161
Zinc, Wt. %	.0856
Phosphorus, Wt. %	.0768
API Performance	SN+
Blend Site	PA
GM dexos1 [®] License Number	D10840IF198



Tilley Company Inc.

1211 Belmar Drive Belcamp, MD 21017
410-574-4500
www.tilleylubricants.com