

MileGuard[™] TO-4 Drivetrain Oil

MileGuard TO-4 Drivetrain Oils are formulated to meet the stringent performance requirements of the Caterpillar TO-4 specification. These fluids are recommended for equipment where specified TO-4 qualified oils are required in order to maintain the Caterpillar equipment warranty. MileGuard TO-4 Drivetrain Oils are blended to provide superior gear wear protection and excellent thermal stability while maintaining a delicate balance of static and dynamic frictional characteristics with a variety of materials to give smooth transmission power transfer under high horsepower conditions. The balanced additive package provides substantially improved load carrying capacities and durability and reduces brake chatter. MileGuard TO-4 Drivetrain Oils provides excellent service in all Caterpillar powershift transmissions, final drives, hydrostatic transmissions, torque converters, hydraulics or any system which specify TO-4 qualified oils.

Benefits

- Extends component life
- Excellent gear protection
- Oxidation and thermal stability for long life
- Excellent rust and corrosion protection Improved friction and anti-wear performance compared to TO-2 fluids

Meets or Exceeds

- Caterpillar TO-4
- Allison C-4 ((10W & 30W)
- Komatsu Dresser
- Komatsu Micro-Clutch
- ZF TE-ML 03C (10W & 30W)
- Eaton Vickers EH-102C
- Temec/TCC
- Dana Powershift
- API GL-3





MileGuardTM TO-4 Drivetrain Oil

Typical Characteristics:

SAE VISCOSITY GRADE	10	30	50
Gravity, API	29.6	27.6	25.5
Viscosity			
@ 40 °C, cSt	41	101	248.5
@100 °C, cSt	6.34	11.5	20
@ 100 °F, SUS	191.3	468	1151
@ 210 °F, SUS	47	64.6	98.5
Viscosity Index	102	101	93
Flash Point °F	435	460	500
Copper Strip Corrosion	Pass	Pass	Pass
Foam Test	Pass	Pass	Pass

